

## Technical specifications

### MARMOLEUM® click

Marmoleum click meets the requirements of EN 14085 (floor panels) and EN 548 (linoleum)



Classification	EN 685	23/32
Dimensions (length x width)	EN 427	panel: 910 mm x 300 mm, square: 300 mm x 300 mm
Static charge	EN 1815	< 2 kV
Fire rating	DIN 4102-1	Class C <sub>0</sub>
Castor chair resistance	EN 425	Suitable for office chairs with castors.
Residual indentation	EN 433	0.07 mm typical value
Effect of a furniture leg	EN 424	No visual damage
Colour fastness	ISO 105-B02	Method 3: blue scale minimum 6. Depending on the colour, the colour fastness is usually higher, often being 8 (blue scale maximum is 8). The samples may differ slightly from the Marmoleum click/click square supplied.
Thermal conductivity	EN 12524	± 0.08 m <sup>2</sup> k/W
Chemical resistance	EN 423	Resistant to diluted acids, oils, fats and to the conventional solvents such as alcohol, white spirit, etc. Not resistant to prolonged exposure to alkalis.
Bacteriostatic properties	EN ISO 846	Marmoleum has bacteriostatic properties, which are confirmed by independent laboratories, even against the bacteria MRSA.
Dimensional stability	EN 13 329	max. 0.6 mm
Cigarette resistance	EN 1399	Marks left on Marmoleum click/click square as a result of stubbed-out cigarettes can be easily removed with slight abrasive cleaning. Marmoleum does not melt.
LCA	Life Cycle Assessment	✓

The above information is subject to modifications for the benefit of further improvements.